



TIMES-2™ QUIK-PANEL SLATWALL

PRODUCT SUMMARY:

Unique accessory to the Aurora Times-2™ Rotary Storage unit, the Aurora Times-2 Quik-Panel Slatwall side panel provides storage, staging, and display capability to the end panels of the Times-2 cabinet. It is available on all Aurora Times-2 Rotary Storage units two tiers high and above, in both letter and legal depths. The Quik-Panel can be installed on the right, left, or both sides.



PRODUCT FEATURES AND BENEFITS:

- Compatible with all common commercially available Slatwall items. Provides easy and convenient attachment for a wide variety of hooks and accessories.
- Increase storage capacity. Add storage to outside of unit with reconfigurable bins, hooks, etc.
- Increase flexibility. Add a presort/staging or display area outside of the storage unit.
- Coordinates with any décor. Choose from the Aurora standard WilsonArt laminate selection.
- Or choose from the standard Aurora Wood-Tek species and finishes to coordinate with other millwork or Wood-Tek items.
- Order this accessory for new Times-2 units or easily retrofit to existing units.
- Compatible with the Times-2 Caster Kit for more versatility and portability. (see photo)
- Compatible with the Times-2 Quik-Station when located above or on the opposite side of the rotary cabinet.
- Mounting hardware is included.

TECH SPEC:

The Aurora Times-2™ Quik-Panel Slatwall panel shall consist of a Slatwall panel with a high-density MDF core board faced with a WilsonArt vertical grade laminate or a wood veneer to a nominal thickness of $\frac{3}{4}$ inch (19 MM). Panel shall be edged on two vertical sides with a solid wood frame edge $\frac{3}{4}$ inch (19 MM) by $1\frac{1}{2}$ inch (38 MM). Panel shall have slot inserts of either black plastic or silver anodized aluminum to distribute accessory point load. The Slatwall panel shall be made available for all letter and legal depth Times-2 Rotary Storage units two tiers high and greater. The height of the panel shall vary in proportion to the height of the Aurora Times-2 Rotary Storage unit on which it is to be mounted. Full height panels shall be mounted flush with the top of the rotary storage unit and extend down to be flush with the bottom edge of the Times-2 base. Partial height panels shall be mounted flush with the top of the rotary storage unit and be available in heights of 2 foot (610 MM), 3 foot (914 MM), and 4 foot (1219 MM). Slatwall panels shall be compatible with the Times-2 Quik-Station work surface accessory when the unit height is great enough to allow for a partial height panel to locate above the Quik-Station with a minimum working height of 29 inches (737 MM) when locating on the same side of the storage unit. Quik-Panel Slatwall panels shall be compatible with the Quik-Station when locating on the opposite side of the storage unit. All Quik-Panel Slatwall panels shall be compatible with the Times-2 Caster Kits.